




Motorola Moto G4 Plus Rear Camera Replacement

Use this guide to replace the rear camera in your Motorola Moto G4 Plus.

Written By: Turki Al-Mulla



INTRODUCTION

This guide will walk you through the process of replacing the rear camera in a Motorola Moto G4 Plus phone.



TOOLS:

- [Spudger](#) (1)
- [Tweezers](#) (1)
- [T4 Torx Screwdriver](#) (1)



PARTS:


- [Moto G4 Plus Rear Camera Replacement](#) (1)

Step 1 — Battery



- Hold your Motorola G4 Plus face down. Pry off the rear cover using a spudger or your fingers.

Step 2




- Using a T4 screw driver, remove the nineteen 3mm screws securing the rear housing.

Step 3




- Remove the small silicon cover to the left of the camera using tweezers.
- Using the spudger tool, lift up the cable found underneath the silicon cover.
- Remove the back panel assembly.

Step 4



- Using tweezers, remove the yellow stickers and black film connecting the battery to the motherboard.

Step 5





- Using tweezers, disconnect the red and black battery cable from the motherboard.

Step 6




- Pry off the battery using a spudger.
- ⓘ The battery is kept in place with a strong adhesive. It may require some jostling to remove.

Step 7 — Motherboard



- Using tweezers, lift up the black silicon piece connecting the motherboard to the front casing.
- Using tweezers, remove the red and black cable connecting the motherboard to the front casing.

Step 8




- Using a spudger, remove the two metal pieces connecting the motherboard to the front casing.

Step 9



- Using tweezers, remove the yellow film connecting the rear camera to the motherboard.
- ⓘ The film is connected by an adhesive, so it may take some jostling to remove.

Step 10




- Using a T4 screwdriver remove the two 4mm screws connecting the motherboard to the front casing.

Step 11




- Using a spudger, lift up and remove the motherboard.

Step 12 — Rear Camera




- Using tweezers, remove the yellow film connecting the motherboard to the rear camera.

Step 13



- Using a spudger, lift up the metal connecting piece.

Step 14



- Using tweezers, pull up and remove the rear camera.

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-06-25 07:40:39 PM.